

# UCERSA

## SUPREME AIRLESS 4.0

### MAIN CHARACTERISTICS

Suitable for any type of ceramic glaze  
Two versions are available: version with 1 motor and version with 4 independent motors  
High performance controller  
User friendly  
Automatic motor stand by Stand when the line stop  
Automatic glaze save mode when in stand-by Whe the tile does not arrive anymore for the set time, pump work at low speed (energy saving, nozzle wear saving, glaze saving) returning immediately to the set pressure upon material return (function available only with SERTAM Automatic Airless Pump)  
Complete with protective casing

### TECHINCAL FEATURES

Frame entirely stainless steel made  
Brushless motor Sanyo Denky  
Electrical panel IP65  
Max speed 145 cycle per minute  
Min tile size 700 mm, opening 900 mm  
Max tile size 1.700 mm, opening 2.000 mm



Supreme 4.0 is the station for application of glaze, engobes, crystalline and grits on big size from 700 mm up to 1700 mm equipped with 4 totally independent Brushless motors, for each of which the operator can freely choose and set the speed and synchronization, getting easily the desired effect on the product.

[www.ucersa.com](http://www.ucersa.com)

C/L'Alcora (Prol. S. Jaime), s/n, 12550 - Almazora (Castellón) Telf +34 964 503 333 - fax 964 550 712 - [ucersa@ucersa.com](mailto:ucersa@ucersa.com)

supreme airless 4.0